

POWER TOOL SOLUTIONS



AUDIA® ELASTOMERS
An AUDIA® Company

BUILD ON OUR EXPERTISE.

All grades are:

- RoHS, REACH, Prop 65 compliant
- UL File Number – E242215
- HB Flame Rating
- Black or Natural color

All grades offer:

- Chemical resistance
- Wear resistance
- -40°C to 70°C operating temperature
- Haptic user-interface
- Cohesive bond to substrate

	● Durometer	● Bonds To
TPE-350 Series	● 60 - 80A	● PC/PBT OM
TPE-350A5 Series	● 60 - 80A	● PC, ABS & PC/ABS OM
TPE-360 Series	● 60 - 80A	● PA & GF PA
TPE-261 Series	● 50 - 90A	● PP & GF PP OM

Additional Options: Unique Over-Molding Solutions

- Tritan, POM, Nylon, ABS & PC
- PCR content up to 50%
- BIO content up to 50%
- Oil resistance
- Antimicrobial versions
- Custom colors



www.audiaelastomers.com

The information contained in this brochure is provided "as is" and without any warranties of any kind, whether express or implied, including but not limited to implied warranties of merchantability and/or fitness for a particular use. This document is for general information purposes only and does not constitute advice or an offer to sell specific products. Information contained herein is subject to change based on product specifications. © 2024 Audia Elastomers PL_20240214