

## ORDERING

### Available as Cat. No.

220-5000TC	AirChek TOUCH Pump only
220-5000TC-S	Starter Pump Kit
220-5000TC-K	Single High Flow Pump Kit
220-5000TC-KD	Single High/Low Flow Pump Kit
220-5000TC-K3D	3-pack High/Low Flow Pump Kit
220-5000TC-K5D	5-pack High/Low Flow Pump Kit

"Pump only" requires charging cradle and power supply that is included in kits.  
See more at [www.skcinc.com/touch-pumps](http://www.skcinc.com/touch-pumps).

### Recommended Calibrator<sup>†</sup>

375-0550N	chek-mate with NIST standard traceable calibration certificate
375-0550	chek-mate with UK standard traceable calibration certificate

375-0550-KN	Kit with chek-mate and pulsation dampener for CalChek full calibration and NIST certificate
-------------	---

<sup>†</sup> Calibrators and Kit available with ISO standard traceable calibration certificate. Contact SKC for details.

### Recommended Accessories

877-93	DataTrac Pro for AirChek TOUCH Hardware Accessory Kit (free software download)
210-500	Low Flow Adapter Kit
375-200	CalChek Communication Cable (required for CalChek automatic calibration with chek-mate)



Standard Cradle



e-Cradle

Charging, CalChek calibration, and PC communication

For ordering details and additional accessories, visit [www.skcinc.com/touch-pumps](http://www.skcinc.com/touch-pumps)

## CalChek Automatic Calibration

Get fast, easy, and accurate field calibration with the patented\* CalChek feature in AirChek TOUCH Sample Pumps and the Medium Flow chek-mate Calibrator!

**No manual adjustments**

**Calibrate a single flow point pre and post-sampling**

**Calibrate across a range of flows following repair/maintenance**

**Document calibration with DataTrac Pro Software**

**See ordering above. Don't forget the CalChek Communication Cable!**

\* U.S. Patent Nos. 6,227,031 and 6,363,769

# AirChek **TOUCH**

## SAMPLE PUMP



**Flows from 5 to 5000 ml/min**

**TOUCH screen for intuitive operation and calibration — the easiest pump you will ever use**

**Powerful battery provides over 20 hours of run time**

**Features to help you power through multiple sampling applications**

**Hands-free calibration with SKC CalChek Cable and Medium Flow chek-mate Calibrator**



Easy navigation on color touch screen



Full programmability – on PC or touch screen



Automatic calibration



SCIENCE. SERVING PEOPLE.

SKC Inc. 724-941-9701 | SKC-West 714-992-2780 | SKC South 434-352-7149

[www.skcinc.com](http://www.skcinc.com)



SCIENCE. SERVING PEOPLE.

[www.skcinc.com](http://www.skcinc.com)

# AirChek **TOUCH**

## 5 to 5000 ml/min Sample Pump

### KEY FEATURES

#### Extended flows from 5 to 5000 ml/min

- 5 to 500 ml/min with low flow accessories
- Multi-tube sampling in low flow mode

#### High back pressure compensation

#### Automatic flow correction for changes in temperature and atmospheric pressure

#### Full programmability from easy-to-use color touch screen or from PC with DataTrac Pro Software

#### CalChek automatic calibration with chek-mate calibrator - see more on page 4!

#### Flow fault and auto-restart

#### Powerful Li-Ion battery lasts multiple shifts

#### Rugged and secure

#### Ultra quiet

#### Chainable charging cradles – use one power source

#### Advanced reporting from DataTrac Pro Software

#### Intrinsically safe

#### Designed to meet ISO 13137

### Selection Guide

AirChek®	AirChek <b>ESSENTIAL</b>	AirChek <b>TOUCH</b>	AirChek <b>CONNECT</b>
Listed Intrinsically Safe	•	•	•
Operation	Touch keypad	Color touch screen	Touch screen
Programmable		•	•
PC Compatible – Download History		•	•
Bluetooth			•
Mobile App			•
Compensates for Changes in Temperature and Atmospheric Pressure	•	•	•
Flow Fault/Auto-restart	•	•	•



### PERFORMANCE PROFILE

Flow Range	Constant flow from 1000 to 5000 ml/min (5 to 500 ml/min requires low flow tube holder)
Compensation Range (back pressure capability)	5000 ml/min at 20 inches water back pressure 4000 ml/min at 30 inches water back pressure 3000 ml/min at 40 inches water back pressure 2000 ml/min at 50 inches water back pressure 1000 ml/min at 50 inches water back pressure
Flow Control System	Isothermal, corrects for changes in back pressure, temperature, and atmospheric pressure
Flow Fault/Auto-restart	If unable to compensate, pump goes into flow fault mode and tries restart 5 times.
Power	Removable rechargeable Lithium-ion (Li-Ion) battery, 7.4 V, 2.6 Ah, 19.2 Wh or AC using cradle
Run Time	20+ hours at 2000 ml/min <sup>‡</sup> 10 hours at 5000 ml/min <sup>‡</sup> Indefinite run from charging cradle
Charging Time/Charging Method (varies with battery capacity and level of discharge)	Approximately 3 hours/charge via cradle, available as a single unit using Single Cradle Power Supply Cat. No. 220-600; chainable up to 5 units using a Multi Cradle Power Supply Cat. No. 220-700
Accuracy	Flow control: 5% of set-point after calibration to desired flow Atmospheric pressure: ±0.3 in Hg Temperature: ±1 C
Temperature Ranges	Operating: 32 to 104 F (0 to 40 C) Charging: 32 to 113 F (0 to 45 C) Storage: -4 to 113 F (-20 to 45 C)
Humidity Ranges	Operating: ≤ 95% RH, non-condensing Storage: ≤ 95% RH, non-condensing.
Altitude	Corrects flow for changes in temperature (32 to 104 F [0 to 40 C]) and ambient pressure up to 15,000 feet (4,572 meters) above and down to 4,500 feet (1,372 meters) below sea level
Display/Parameters	Color LCD/real-time flow rate, ambient temperature, ambient pressure, accumulated volume, elapsed time
User Interface	Resistive touch screen with auto-dim and locking options
Sound Level	Avg. 51.7 dB at 3-ft (1-m) distance using a 37-mm, 0.8-µm MCE filter cassette
Tubing	Requires 1/4-inch ID tubing
Dimensions	4.1 x 3.7 x 2.8 in (10.4 x 9.4 x 7.1 cm)
Weight	19.4 oz (550 gm)
Certifications	<ul style="list-style-type: none"> <li>• Intrinsic safety: UL Class I, Div. 1, Groups A,B,C, and D; Class II, Div. 1, Groups E,F, and G; Class III, Div. 1 hazardous locations when used with SKC battery pack Cat. No. P75718; T-Code T3C. Exia; Class I, Zone 0 Gp IIC (SKC Cat. No. 220-5000TC)</li> <li>• CE, UKCA</li> <li>• Designed to meet ISO 13137:2013</li> </ul>
Case Material	Polycarbonate with rubberized anti-static overmolding

<sup>‡</sup> Tested using 37-mm, 0.8-µm MCE filter with new pump and battery. Pump performance may vary.



SCIENCE. SERVING PEOPLE.

[www.skincinc.com](http://www.skincinc.com)



SCIENCE. SERVING PEOPLE.

[www.skincinc.com](http://www.skincinc.com)